


Domo Visión Nocturna

RS403

dLux[®]
Equipos y Accesorios para Video- Vigilancia

- Effio platform
- 650TV Lines
- Super HAD high sensitivity WD CCD



RYK-S403



RYK-S403
(Vandal Proof)

VIDEO	
Image Device	1/3" Color Sony Super HAD Double-Density WD CCD
Picture Elements (HxV)	NTSC:976x494, PAL:976x582
Resolution	650 TVL
Illumination	0.01 Lux(Day mode), 0.003 Lux (Night mode), 0.0003Lux (DSS) / F1.2
S/N Ratio	More than 50dB
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/100,000 include Flickerless (NTSC:1/100, PAL:1/120)
Gamma	0.45
LENS	
Lens Furnished	2.8~10.5mm / F1.2~2.6, Wide:99.5°x73.2°, Tele:27.4°x20.6° (HxV)
Iris Control	DC Drive
FUNCTIONS	
IR-Cut filter Removable	Yes
Wide Dynamic Range	On / Off (Level adjustable), Auto detection
Digital Noise Reduciton	Low / Mid / High
Day & Night (ICR)	AE / Day / Night / EXT
Day & Night I/O	Input / Output
On-Screen-Display (OSD)	English / Simple Chinese
Digital Slow Shutter (DSS)	Off, 2~20, 40, 80, 160, 256 FLD
Flickerless Mode	On / Off (NTSC:1/100, PAL:1/120)
Motion Detection	24*16 detection blocks
Privacy Masking	15 Areas (Area size adjustable)
White Balance	Auto / Indoor / Outdoor / Manual / Push Auto
Gain Control	Auto / Manual
Back Light Comp.	On / Off (7 Areas & Smart Area, Level:0~255)
Digital Zoom	16x
Camera ID	000~255
Camera Title	Up to 16 characters
Mirror	Horizontal / Vertical / Rotate
Freeze	On / Off
Positive / Negative	On / Off
GENERAL	
Infrared Luminary	24 pieces IR-LED
Wavelength	850nm
Illumination Distance	Max. 20M
Weatherproof	Yes
Remote Control	RS-485/422
Protocol	PELCO D&P
Sync. System	Internal / External Line Lock
Video Output	1 Vp-p / 75 Ohms
Power Supply	DC12V±10%, DC12V/AC24V Dual
Power Consumption	5.28 W max.
Operating Temp.	-10°C ~ 50°C