

DXL-CM28

Features:

- IR Bullet Camera
- 1/2.7 CMOS 2.0M/1080P
- IR LED: 18pcs SMD LED
- IR Distance:20M
- 2.8mm fixed Lens
- Water Resistant Rate: IP66



Specification

| | | |
|-----------------------|--|---------------|
| Power System | PAL | NTSC |
| Model | ACAT200FA (P) | ACAT200FA (N) |
| Sensor | AR0237 1/2.7 | |
| DSP | D+(| |
| Active Pixel | 1920*1080 | |
| SYNC. | Internal | |
| Resolution | 1080P | |
| VIDEO. OUT | A/T/C/CVBS | |
| Minimum Illumination | 0.01Lux (F1.2) | |
| Gama adjust | 0, 45 | |
| Electric Shutter | 1/50s-1/10000s | |
| S/N Ratio | 48dB(min) (AGC closed) | |
| WDR | OFF/ON | |
| DNR | 2D-DNR | |
| WHITE Balance | ATW/MWB | |
| AE MODE | GLOBE/BLC | |
| OSD | Yes | |
| Coaxial | Yes | |
| Language | Eng Chin1 Chin2 Ital Spain | |
| Day/Night | Ext Color、B/W | |
| Power Input | DC12V ±1V | |
| Power Dissipation | /(%0 (P2 | |
| Transmission distance | 75-5 300M | |
| Operation Temperature | Temperature -10°C ~+55°C, Humidity less than 85%RH | |
| Dimension | 32*32/38*38*1.6 (H) | |