

# DLX12D60006

Product Name		12VDC 6 Way Power Adaptor	
		<b>Features:</b> * 96-264V Wide range input. * High efficiency, long service life, high reliability, high cost performance. * Built-in EMI wave filter. * 100% full load burn-in test. * Good automatic protection for over voltage, over current, overloads and overheats.	
Model	DLX12D60006		
OUTPUT	DC Voltage	12V	
	Rated Current	6A	
	Current Range	0~6000mA	
	Rated Power	72W	
	Ripple & Noise (mv-pp)	Peak to peak voltage(Vpp) <240mV	
	No-load Voltage Range	12V	
	Regulation Accuracy	±10.0%	
	Output Hold-up Time	< 1.5S (230VAC input, full load)	
	Output Hold-up Time	> 50mS(230VAC input, full load)	
INPUT	Voltage Range	96-264VAC	
	Frequency Range	47-63Hz	
	Efficiency(Typ.)	> 80%	
	AC Input Current (Max.)	<1.5A	
	Set-up Impulse Current(Typ.)	<40A@230Vac cold start	
PROTECTION	Shout Circuit	fuse	
ENVIRONMENT	Operating Temp. & Hum.	-10 ~50 , 20%-90%RH (non-condensing)	
	Storage Temp. & Hum.	-40 ~85 , 20%-95%RH (non-condensing)	
SAFETY & EMC	Safety Standards	GB4943, IEC/EN/UL/CSA60950	
	Insulation Resistance	input-output, output-housing, output-housing: 500VDC/100M	
	Electromagnetic Interference	Compliance to EN61000-4; ENV50204, Grade A light industry standard	
OTHERS	Dimension (L*W*H mm)	133*56*42	
	Packing	White box	
	Cooling	Free Air Convection	
	Net Weight (g)	240g	