

DLXV42

Features

- Cámara tipo bullet
- Chip (IMX291 1/2.8)
- Tecnología Starlight
- DWDR
- Resolución 1080P
- 1/2.8"Sony Sensor 2.0M
- IR LED 42
- IR Distancia: 40M
- 2.8-12mm lente varifocal
- Resistente al agua: IP66



Specification

Power System		NTSC
Model		SNCAT200U(N)
Sensor	IMX291 1/2.8	
DSP	NVP2441H	
Active Pixel	1920*1080	
SYNC.	Internal	
Resolution	1080P	
VIDEO.OUT	A-H/A-L/960H PAL/NTSC	
Minimum Illumination	0.0001Lux(F1.2)	
Gama adjust	0.45	
Electric Shutter	1/30s-1/60000s	
S/N Ratio	48dB(min)(AGC closed)	
DEFOG	OFF/AUTO	
AGC	Level 0-15	
SENS UP	OFF/2X-30X	
D-WDR	ON(0-8)/AUTO/OFF	
BLC	OFF/HSBLC/BLC	
WHITE BAL	ATW/AWC-SET/Indoor/Outdoor/MANUAL/AWB	
2D-NR	LOW/MID/HIGH/OFF	
3D-NR	LOW/MID/HIGH/OFF	
MIRROR	OFF/ON	
FLIP	OFF/ON	
OSD	Yes	
Coaxial	Yes	
Language	Eng CHN1/2 GER FRA ITA SPA POL RUS POR NED TUR	
Day/Night	Auto、Color、B/W、Ext	
Motion Detection	4 areas optional	
Privacy Zone	4 areas optional	
Defog	OFF/AUTO	
Power Input	DC12V±1V	
Power Dissipation	70mA-80mA	
Transmission distance	75-5 300M	
Operation Temperature	Temperature -10 ~ +55 ,Humidity less than 85%RH	
Dimension	32*32/38*38*1.6(H)	

Dimension Chart

